




**QI TECH INC.**

**a subsidiary of Changshun**

QI TECH INC.

7410 Ambassador Row, Dallas, Texas 75247

www.qitechinc.com



## PRODUCT INFORMATION

### BASIC CABLE INFORMATION:

Part Number: DLB3632

Type and Specification: ETP 36-18AWG

Packing Information: 500 meter per reel

Cable Color: Gray.

### APPLICATION:

Elevator suspension cable for indoor and panoramic elevators.

### INSTALLATION:

To comply with the correct installation procedures please refer to the Changshun Product Catalog which is available separately, for the DLB3632 cable, secure it with the PX25500AV4-B nylon cable clamp during mounting.

### THE COMPOSITION STRUCTURE AND SPECIFIC INFORMATION OF CABLE ARE AS FOLLOWS:

|                       |                     |                          |
|-----------------------|---------------------|--------------------------|
| Component             | 36/18AWG            | Strength Member          |
| Core Wire             |                     |                          |
| Material              |                     | Aircraft Steel Wire Rope |
| Conductor Material    | TR Soft Copper Wire |                          |
| Insulation Material   | PVC Class 4         |                          |
| Shielded Material     |                     |                          |
| Inner Sheath Material |                     |                          |
| Outer Sheath Material | PVC Class 1.5       |                          |

Note: The diameter of the wire rope is  $\phi$  3.0mm.

### THE CONDUCTOR NUMBERING ARE AS FOLLOWS:

|        |                            |
|--------|----------------------------|
| Size   | Conductor Number And Color |
| 18 AWG | Black 1 to 36              |

### THE MECHANICAL PROPERTIES:

|                                           |            |
|-------------------------------------------|------------|
| Maximum Freely Suspended Length (ft[mm]): | 702[214]   |
| Maximum Travelling Height(ft[mm]):        | 1404[428]  |
| Maximum Running Speed(m/s):               | 10         |
| Acceleration:                             |            |
| Operating Temperature(°C):                | -20 to +60 |
| Recommended Loop Diameter(mm):            | 368[±100]  |

|                                           |                         |
|-------------------------------------------|-------------------------|
| Cable Net Weight Approx. (lbs/ft [kg/m]): | 0.9[1.3]                |
| Overall Dimensios Approx. (W/H, in [mm]): | 2.22 / 0.36[56.3 / 9.2] |
| Copper Content.(lbs/kft [kg/km]):         | 252.53[375.80]          |
| Flame property:                           | FT1                     |

THE ELECTRICAL PROPERICAL:

|                                                          |       |
|----------------------------------------------------------|-------|
| Maximum Voltage:                                         | 300V  |
| Twisted Pair Attenuation Characteristics.(dB/100m):      |       |
| Coaxial Cable Attenuation Characteristics.(dB/100m):     |       |
| Fiber Optic Cable Attenuation Characteristics.(dB/100m): |       |
| Coaxial Cable Transfer Impedance.(Ω/km):                 |       |
| The conductor resistance of the 14 AWG(Ω/km):            | ≤8.88 |
| The conductor resistance of the 18 AWG(Ω/km):            | ≤22.4 |
| The conductor resistance of the 20 AWG(Ω/km):            | ≤35.7 |

CERTIFICATION & STANDARDS

|                  |                                                                                                                                                                     |
|------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Certification:   |   |
| CSA File Number: | 253817                                                                                                                                                              |
| CSA Standard:    | CSA C22.2 No.49                                                                                                                                                     |
| UL Standard:     | UL 62                                                                                                                                                               |