



QI TECH INC.

a subsidiary of Changshun

QI TECH INC.

7410 Ambassador Row, Dallas, Texas 75247

www.qitechinc.com

PRODUCT INFORMATION

BASIC CABLE INFORMATION:

Part Number:DLY2668

Type and Specification: Hoistway Cable 2×18AWG

Packing Information: 300 meter per reel

Cable Color: Black

APPLICATION:

Elevator suspension cable for indoor and panoramic elevators.

INSTALLATION:

To comply with the correct installation procedures please refer to the Changshun Product Catalog which is available separately.

THE COMPOSITION STRUCTURE AND SPECIFIC INFORMATION OF CABLE ARE AS FOLLOWS:

Component Core Wire	2/18AWG
Conductor Material	TR Soft Copper Wire
Insulation Material	PVC Class 4
Inner Sheath Material	
Outer Sheath Material	PVC Class 1.5

THE CONDUCTOR NUMBERING ARE AS FOLLOWS:

Size	Conductor Number And Color
18AWG	Black、White

THE MECHANICAL PROPERTIES:

Operating Temperature(°C):	60
Cable Net Weight Approx. (lbs/kft [kg/km]):	33.60[50.00]
Overall Dimensios Approx. (W/H, in [mm]):	0.22[5.6]
Copper Content.(lbs/kft [kg/km]):	10.35[15.40]
Flame property:	FT1

THE ELECTRICAL PROPERICAL:

Maximum Voltage:	300V
The conductor resistance of the 14 AWG(Ω/km):	≤8.88
The conductor resistance of the 18 AWG(Ω/km):	≤22.4
The conductor resistance of the 20 AWG(Ω/km):	≤35.7

CERTIFICATION & STANDARDS

Certification:



CSA File Number:

253817

CSA Standard:

CSA C22.2 No.49

UL Standard:

UL 758、UL1581